

Antenna Specifications

At Wavelink, our aim is to provide timely and comprehensive services to our customers. If you require any assistance, please contact our headquarters:

2nd Floor, Building D, No. 88 Tongqiu Road, Zhangpu Town, Kunshan City, Jiangsu Province, China

Tel: +86-512-57449488

Email: sales@kswavelink.com

Wavelink Certifications:



Wavelink Partners:

Skyworth **NARI**

flex

 **HUAWEI**

 **VVDN**
TECHNOLOGIES

Tenda **Infinova**

dji

Hikvision

JABIL

Catalogue

1	Product Description	3
2	Product Features	3
3	Product Specifications	3
4	Overall Performance	4
5	Product Size	7
6	Others	8

1 Product Description

This wavelink antenna covers WiFi2.4 and WiFi5.8.

2 Product Features

Easy to install
High efficiency
Removable



3 Product Specifications

Passive Electrical Specifications

Frequency Range	2400-2500 MHz 5150-5850MHz
Input Impedance	50 Ω
VSWR	≤ 3

Gain ≤ 3 dBi

Polarization Type Linear

Mechanical Specifications

Antenna Size 275mm × 29mm


Connector Type SMA


Working Temperature -40 °C to +85 °C

Radome Color Black

4 Overall Performance

KEYSIGHT VNA Network Analyzer E5071C 100 kHz – 8.5 GHz






Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	Max (dB)	Min (dB)	Directivity (dBi)	AttH (dB)	AttV (dB)
2400	38.54	-4.14	3.21	1.06	3.21	-36.06	7.35	46.16	46.3
2410	36.77	-4.34	3.16	1.01	3.16	-25.45	7.51	46.26	46.45
2420	32.55	-4.88	2.71	0.56	2.71	-22.6	7.59	46.15	46.32
2430	34.93	-4.57	3.11	0.96	3.11	-22.12	7.68	46.31	46.44
2440	35.11	-4.55	3.15	1	3.15	-20.99	7.7	46.52	46.56
2450	35.87	-4.45	3.26	1.11	3.26	-19.55	7.72	46.77	46.93
2460	34.97	-4.56	3.11	0.96	3.11	-19.23	7.68	46.82	46.89
2470	31.94	-4.96	2.6	0.45	2.6	-22.19	7.55	46.54	46.65
2480	29.09	-5.36	2	-0.15	2	-26.13	7.36	47.04	47.22
2490	25.06	-6.01	1.11	-1.04	1.11	-22.56	7.12	46.75	46.82
2500	23.46	-6.3	0.63	-1.52	0.63	-21.94	6.92	46.91	47.08
5150	14.48	-8.39	-2.03	-4.18	-2.03	-29.56	6.36	52.56	52.6
5200	12.58	-9	-2.51	-4.66	-2.51	-28.61	6.49	52.91	53
5250	11.87	-9.26	-3.34	-5.49	-3.34	-29.57	5.91	53.21	53.29
5300	9.49	-10.23	-5.06	-7.21	-5.06	-24.44	5.17	52.44	52.69
5350	11.97	-9.22	-4.76	-6.91	-4.76	-21.59	4.46	52.64	53
5400	12.39	-9.07	-4.66	-6.81	-4.66	-23.55	4.41	52.74	52.9
5450	15.71	-8.04	-3.02	-5.17	-3.02	-23.67	5.01	53.16	53.14
5500	11.43	-9.42	-4.25	-6.4	-4.25	-36.69	5.17	52.97	52.99
5550	12.95	-8.88	-3.03	-5.18	-3.03	-24.48	5.85	53.13	53.29
5600	10.57	-9.76	-3.43	-5.58	-3.43	-25.92	6.33	53.23	53.61
5650	12.68	-8.97	-3.06	-5.21	-3.06	-29.2	5.91	52.92	53.16
5700	12.91	-8.89	-3.45	-5.6	-3.45	-25.22	5.44	52.98	53.24
5750	14.11	-8.5	-3.1	-5.25	-3.1	-24.78	5.4	53.32	53.6
5800	12.68	-8.97	-2.73	-4.88	-2.73	-20.95	6.24	53.56	53.79
5850	13.93	-8.56	-2.64	-4.79	-2.64	-21.83	5.92	53.5	53.52



5 Product Size



6 Others

DESCRIPTION	SPECIFICATION
Temperature /Humidity cycling	1, The device under test is kept for 30 mins in an environment with a temperature of -40 °C. 2, Kept for 4 Hours in an environment with a temperature of 8cthe conditions are stabilized at room temperature. 3, Parts should meet RF spec before and after test. 4, No cosmetic problem(No soldering problem;No adhesion problem of glue).
Temperature Shock	1, The device under test at -40 °C ⇌ 125 °C by 100 cycles, Dwell of 30 mins, transition time between Dwell 30 secs (~ 61 mins / cycle) and each item should be measured after exposing them in normal temperature and humidity for 24 h. 2, Parts should meet RF spec before and after test. 3, No cosmetic problem(No soldering problem; No adhesion problem of glue).
High Temperature	1, Temperature:125°C, time:1008 hours 2, There is no substantial obstruction to air flow across and around the samples, and the samples are not touching each other 3, Parts should meet RF spec before and after test. 4, No cosmetic problem(No soldering problem; No adhesion problem of glue).
Salt mist test	1, The device under test is exposed to a spray of a 5% (by volume) resolution of NACL in water for 2 hours. Thereafter the device under test is left for 1 week in room temperature at a relative humidity of 95%. The cycle is repeated until a total of 2 cycles have been completed. Here after the conditions are stabilized at room temperature. 2, Parts should meet RF spec before and after test. 3, No visible corrosion. Discoloration accept.