

Antenna Specifications

At Wavelink, our aim is to provide timely and comprehensive services to our customers. If you require any assistance, please contact our headquarters:

2nd Floor, Building D, No. 88 Tongqiu Road, Zhangpu Town, Kunshan City, Jiangsu Province, China

Tel: +86-512-57449488

Email: sales@kswavelink.com

Wavelink Certifications:



Wavelink Partners:

Skyworth NARI

flex

 **HUAWEI**

 **VVDN**
TECHNOLOGIES

Tenda Infinova

dji

Hikvision

JABIL

Catalogue

1	Product Description	3
2	Product Features	3
3	Product Specifications	3
4	Overall Performance	4
5	Product Size	7
6	Others	9

1 Product Description

This wavelink antenna covers 450MHz.

2 Product Features

Easy to install
High efficiency
Removable



3 Product Specifications

Passive Electrical Specifications

Frequency Range	450MHz
Input Impedance	50 Ω

VSWR	≤ 2
Gain	≤ 1 dBi
Polarization Type	Linear


Mechanical Specifications

Antenna Size	470mm × 62mm
Connector Type	SMA
Working Temperature	-40 °C to +85 °C
Radome Color	Black


4 Overall Performance

KEYSIGHT VNA Network Analyzer E5071C 100 kHz – 8.5 GHz






Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	Max (dB)	Min (dB)	Directivity (dBi)	AttH (dB)	AttV (dB)
440	17.28	-7.62	-2.95	-5.1	-2.95	-24.43	4.67	35.42	36.9
441	17.5	-7.57	-2.85	-5	-2.85	-24.72	4.72	35.41	36.88
442	17.68	-7.52	-2.77	-4.92	-2.77	-25.05	4.75	35.41	36.86
443	17.89	-7.47	-2.72	-4.87	-2.72	-25.31	4.76	35.4	36.84
444	18.16	-7.41	-2.65	-4.8	-2.65	-25.55	4.76	35.4	36.82
445	18.54	-7.32	-2.56	-4.71	-2.56	-25.6	4.76	35.39	36.8
446	18.91	-7.23	-2.47	-4.62	-2.47	-25.75	4.76	35.36	36.74
447	19.39	-7.12	-2.35	-4.5	-2.35	-25.74	4.77	35.33	36.68
448	19.96	-7	-2.21	-4.36	-2.21	-25.65	4.78	35.31	36.61
449	20.57	-6.87	-2.07	-4.22	-2.07	-25.5	4.8	35.28	36.55
450	21.2	-6.74	-1.94	-4.09	-1.94	-25.38	4.8	35.25	36.49
451	21.48	-6.68	-1.86	-4.01	-1.86	-25.22	4.82	35.15	36.35
452	21.76	-6.62	-1.8	-3.95	-1.8	-24.9	4.82	35.05	36.21
453	22.05	-6.57	-1.74	-3.89	-1.74	-24.6	4.83	34.95	36.07
454	22.33	-6.51	-1.68	-3.83	-1.68	-24.21	4.84	34.85	35.93
455	22.6	-6.46	-1.61	-3.76	-1.61	-23.77	4.85	34.76	35.8
456	23.52	-6.28	-1.43	-3.58	-1.43	-23.12	4.86	34.79	35.81
457	24.38	-6.13	-1.26	-3.41	-1.26	-22.44	4.87	34.82	35.83
458	25.12	-6	-1.11	-3.26	-1.11	-21.71	4.89	34.84	35.84
459	25.68	-5.9	-0.99	-3.14	-0.99	-21.02	4.92	34.87	35.86
460	26.06	-5.84	-0.9	-3.05	-0.9	-20.88	4.94	34.9	35.87



5 Product Size





6 Others

DESCRIPTION	SPECIFICATION
Temperature /Humidity cycling	1, The device under test is kept for 30 mins in an environment with a temperature of -40 °C. 2, Kept for 4 Hours in an environment with a temperature of 8cthe conditions are stabilized at room temperature. 3, Parts should meet RF spec before and after test. 4, No cosmetic problem(No soldering problem;No adhesion problem of glue).
Temperature Shock	1, The device under test at -40 °C ⇌125 °C by 100 cycles, Dwell of 30 mins, transition time between Dwell 30 secs (~ 61 mins / cycle) and each item should be measured after exposing them in normal temperature and humidity for 24 h. 2, Parts should meet RF spec before and after test. 3, No cosmetic problem(No soldering problem; No adhesion problem of glue).
High Temperature	1, Temperature:125°C, time:1008 hours 2, There is no substantial obstruction to air flow across and around the samples, and the samples are not touching each other 3, Parts should meet RF spec before and after test. 4, No cosmetic problem(No soldering problem; No adhesion problem of glue).
Salt mist test	1, The device under test is exposed to a spray of a 5% (by volume) resolution of NACL in water for 2 hours. Thereafter the device under test is left for 1 week in room temperature at a relative humidity of 95%. The cycle is repeated until a total of 2 cycles have been completed. Here after the conditions are stabilized at room temperature. 2, Parts should meet RF spec before and after test. 3, No visible corrosion. Discoloration accept.